



C-RAM SS

RoHS
Compliant

TECHNICAL BULLETIN 320-7

FREQUENCY-TUNED SALISBURY SCREEN ABSORBER

C-RAM SS is a thin, very light weight, frequency tuned absorber which provides high absorption at specific frequencies.

C-RAM SS is a Salisbury Screen type absorber which is made from a conductive front layer, a dielectric core (or spacer) and a reflective back layer.

The dielectric core is a closed cell polyethylene foam of low loss and low dielectric constant. A reflective aluminum foil back layer is bonded to this core. The front layer is a fiberglass cloth with a lossy coating, it is bonded to the dielectric spacer. This construction provides high tear strength, good abrasion resistance and light weight.

C-RAM SS is readily cut to size with scissors or a band saw. It is well suited to reducing reflections from nearby objects, increasing isolation between adjacent antennas and reducing energy levels of antenna sidelobes.

TYPICAL PROPERTIES

Reflectivity: -20 dB at design frequency
Service temperature: -70 to +180°F
Power handling: 3 W/ft.²
Standard size: 24 in. x 24 in.
(other sizes available)

C-RAM SS is available for frequencies from 1 GHz through 12 GHz. High frequency versions can be fabricated on request.

<u>Band</u>	<u>Nom. Thk.</u>	<u>Nom. Weight</u>
2-4 GHz	1.0 to 0.5 in.	0.24 lbs/ft. ²
4-8 GHz	0.5 to 0.25 in.	0.20 lbs/ft. ²
8-12 GHz	0.25 to 0.10 in.	0.15 lbs/ft. ²

The information in this Technical Bulletin, although believed to be accurate, is not to be taken as a warranty for which Cuming Microwave assumes legal responsibility, nor as permission or recommendation to practice any patented invention without license; it is offered for verification by the customer, who must make the final judgment of suitability for any application.

Document Control No. N-06-000-0123-C
06/13/07 Page 1 of 1